

Minimum Standard Drivers Education Technical Inspection Form

Driver #1 (Please Print): \_\_\_\_\_

Emergency Contact & Phone: \_\_\_\_\_

Driver #2 (Please Print): \_\_\_\_\_

Emergency Contact & Phone: \_\_\_\_\_

Tech Inspector (Please Print): \_\_\_\_\_

Car Make & Model: \_\_\_\_\_ Color: \_\_\_\_\_ Number: \_\_\_\_\_

---

Item(s) Inspected:

\_\_\_\_\_ Helmet: SA 2015, SA 2020, M 2015, or M 20120 rated current or last date certificate, no cracks; chin strap in good condition.

\_\_\_\_\_ Any make of car delivered with factory installed roll over protection meets the minimum standards for DE events. In these cars the soft-top must be in the up position or the hard top installed. If the top is in the down position, approved arm restraint system must be used.

**Late Model Porsche Cabriolets (911s) and Roadsters (Boxsters) Have  
Deploying Rollover Protection and  
DO NOT REQUIRE Roll Bars & Cages for DEs**

\_\_\_\_\_ Roll Bar & Cages: Mandatory for all open & semi-open cars without manufacturer's structural or deploying roll over protection; roll bars must pass the broomstick rule and must be covered with closed cell foam padding in any place where a helmet could come in contact with the bar.

\_\_\_\_\_ Seat Belts: Factory or better installation in both seats; must be securely mounted; belts not frayed; equal restraints for passenger and driver. 4-point harnesses prohibited except Schroth Quick Fit. 5-, 6- and 7-point harnesses must use seat with factory routing holes.

-or-

\_\_\_\_\_ If roll bar or cage installed, 5-point or 6-point harness, competition seat with passages for shoulder, lap, and antisubmarine straps of the harness. Equal restraint for passenger.

-and-

\_\_\_\_\_ If roll bar or cage and harness equipped, a head and neck restraint.

\_\_\_\_\_ Structural Integrity: no loose body or interior parts; no structural rust at or near suspension points.

\_\_\_\_\_ Doors: must be operational from inside and outside.

\_\_\_\_\_ Windshield: no cracks, condition does not impair vision.

\_\_\_\_\_ Mirrors: minimum of single mirror in good condition and securely mounted.

\_\_\_\_\_ Gas Cap: tightly closed and no leakage.

\_\_\_\_\_ Fluids: NO DRIPPING LEAKS of any fluid of any type.

\_\_\_\_\_ Fluid Lines: proper fittings and line condition; no external clamps used on pressurized oil lines.

\_\_\_\_\_ Battery: properly secured; no apparent corrosion.

\_\_\_\_\_ Throttle Return: freely operating and proper spring(s).

\_\_\_\_\_ Engine: proper exhaust in good condition; general condition of engine and accessories.

\_\_\_\_\_ Belts: fan and other auxiliary belts in good condition with proper tension.

\_\_\_\_\_ Brakes: Sufficient brake pads (5mm or 3/16 inch minimum); rotors and pads are in good condition; no cuts or abrasions in brake lines. There should be no visible cracks extending to the edge of the rotor. With co-driver, pads should exceed minimum standard.

\_\_\_\_\_ Brake Fluid: Sufficient brake fluid; premium fluid recommended. Brake fluid should be changed in accordance with manufacturers recommendations and more frequently for tracked cars. Date brake fluid was last changed: \_\_\_\_/\_\_\_\_/\_\_\_\_. Brakes lines recently bled. Date brakes bled: \_\_\_\_/\_\_\_\_/\_\_\_\_.

\_\_\_\_\_ Brake Lights: functional and visible brake lights.

\_\_\_\_\_ Pedals: All pedals must have free return and be in good operating condition. Brake pedal must be firm.

- \_\_\_\_\_ Wheels-Overall Condition: no cracks, bends or flaws; valve stems must have airtight caps.
- \_\_\_\_\_ Wheel Bolts & Lugs: all lug nuts engaged; pay special attention to after-market wheels & Turbo Twist wheels; if using track tires, steel lug nuts should be used.
- \_\_\_\_\_ Wheel Centerlocks: make sure locking devices are fully engaged.
- \_\_\_\_\_ Wheel Bearings: proper free rotation; no looseness in hub.
- \_\_\_\_\_ Front Suspension: no excessive play; ball joints and tie rods secure; boots and all seals in good condition.
- \_\_\_\_\_ Rear Suspension: half shaft boots in good condition; mounting hardware in good condition; no leakage.
- \_\_\_\_\_ Exhaust System: securely fastened and in good condition.

Tech Inspector                      Signature: \_\_\_\_\_ Date: \_\_\_\_\_

THE UNDERSIGNED INDIVIDUAL(S) HEREBY CERTIFY THAT:

1. This OFFICIAL TECHNICAL INSPECTION FORM (THE "FORM") submitted to the in connection with the Spokane Festival of Speed open lapping event on June 3, 2022 was performed on the date shown below by a Porsche mechanic or other person authorized to conduct such an inspection.
2. The completed Form correctly and accurately shows the condition of the Car identified above on the date of the inspection.
3. There have been no changes in the condition of the Car since the date of the inspection that would affect the track-worthiness of the Car. The undersigned hereby agrees to defend, indemnify and hold harmless PCA and Festival of Speed as well as the inspector, from any and all claims or demands arising directly or indirectly from any incorrect and/or inaccurate statements set forth in this form.

I understand that the technical inspection performed on my Car and my helmet is solely for the purpose of meeting minimum standards of car preparation for the Event. No warranties or guarantees are implied or expressed by the passing of the inspection performed. I acknowledge that the safe condition and operation of my Car is entirely my responsibility. I take full and sole responsibility for any vehicle problems, malfunctions, or damage that may occur in connection with the operation or performance of my Car prior to, during, or subsequent to the Event.

Driver #1 Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Driver #2 Signature: \_\_\_\_\_

---

---

Minimum Standard Grid Tech List:

- \_\_\_\_\_ 1. No loose objects or distracting items
- \_\_\_\_\_ 2. At least one functioning brake light
- \_\_\_\_\_ 3. Gas cap & battery secure
- \_\_\_\_\_ 4. Wheel lug nuts torque
- \_\_\_\_\_ 5. Helmet with proper Snell rating
- \_\_\_\_\_ 6. Proper clothing attire per regional rules
- \_\_\_\_\_ 7. Car numbers in place
- \_\_\_\_\_ 8. Tires must be in good condition with no cracks and/or cuts
- \_\_\_\_\_ 9. Sufficient brake pad thickness